



FZ6 Stereo Zoom Microscopes



FZ6 Stereo Microscope Configurations

Viewing Heads

45° inclined viewing heads rotate 360°. Interpupillary distance adjustable from 54mm - 76mm.

- Binocular
- Binocular with Detent (for measurement)
- Trinocular
- Trinocular with Detent (for measurement)

On trinocular models when beam splitter is engaged light is directed to the camera port and left eyetube (right eyetube goes dark).



Focusing Holders

Two precision guide rack and pinion focusing holders are available, each with adjustable tension. Focus range of 50mm. Choose from coarse focus only or coarse and fine focus for more precision work at higher magnifications. Post Size Ø32mm, focus holder Ø76mm.




Track Stand



Articulated Arm Stand




Reflected & Transmitted LED Track Stand



Track stand with bright, LED illumination.


- Top LED light has 15 LEDs.
- Bottom LED light operates independent of top.
- 100~240V

Ball Bearing Boom Stand



Available with a solid square base or with a clamping table mount.

Boom Stand



Available with a solid square base or with a clamping table mount.

Post Stand



Low Profile Base

FZ6 Stereo Microscope Magnification Chart

Auxiliary Lens	Working Distance	10x Eyepieces		15x Eyepieces		20x Eyepieces	
		Magnification	Field Size	Magnification	Field Size	Magnification	Field Size
1x (Built-In)	100mm	6.7x - 45x	32.8mm - 4.9mm	10.1x - 67.5x	23.9mm - 3.6mm	13.4x - 90x	17.9mm - 2.7mm
0.5x	177mm	3.4x - 22.5x	65.7mm - 9.8mm	5x - 33.8x	47.8mm - 7.1mm	6.7x - 45x	35.8mm - 5.3mm
0.7x	120mm	4.69x - 31.5x	46.9mm - 6.98mm	7x - 47.25x	34.1mm - 5.1mm	9.38x - 63x	25.6mm - 3.8mm
1.5x	47mm	10.1x - 67.5x	21.9mm - 3.3mm	15.1x - 101.3x	15.9mm - 2.4mm	20.1x - 135x	11.9mm - 1.8mm
2x	26mm	13.4x - 90x	16.4mm - 2.4mm	20.1x - 135x	11.9mm - 1.8mm	26.8x - 180x	9mm - 1.3mm



Auxiliary Lenses

Four auxiliary lenses are available for increasing working distance or adjusting magnification.

Eyepieces

High eyepoint, widefield, focusable eyepieces:

- WF10x/22mm with reticle retaining ring.
- WF15x/16mm with reticle retaining ring.
- WF20x/12mm.



C-Mount Adapters

Focusable c-mount adapters for camera connection include:

- 0.35x focusing c-mount
- 0.5x focusing c-mount

FZ6 Stereo Microscope Illumination Options

Dual LED Pipe Light



2



3



- 1 Stand alone LED dual pipe light
- 2 Track stand clamping LED dual pipe light
- 3 Post stand clamping LED dual pipe light

4-Quadrant LED Ring Light



72 LED lights provide cool, bright illumination. Each of 4 quadrants can be turned on or off to control glare.

150w Halogen Ring Light



High Intensity LED Ring Light

150w Halogen Dual Pipe Light



35w LED light with flexible light guide and variable intensity control. 110v~240v.

FZ6 Stereo Microscope Specifications

Optical System	Greenough Optical System
Viewing Head	45° inclined binocular head rotates 360°. Interpupillary distance adjustable 54~76mm. Available with or without detent.
	45° inclined trinocular head rotates 360°. Interpupillary distance adjustable 54~76mm. Beam splitter sends light 100% to eyepieces or to left eyetube and camera port while right eyetube goes dark. Available with or without detent.
Eyepieces	WF10x-F widefield, high eyepoint, focusing eyepieces, FN22, with reticle retaining ring for 24mm diameter reticle.
	WF15x-F widefield, high eyepoint, focusing eyepieces, FN16, with reticle retaining ring for 24mm diameter reticle.
	WF20x-F widefield, high eyepoint, focusing eyepieces, FN12.
Objective Lenses	Standard built-in objective: 0.67x - 4.5x zoom.
	Auxiliary objective 0.5x, WD = 177mm.
	Auxiliary objective 0.7x, WD = 120mm.
	Auxiliary objective 1.5x, WD = 47mm.
Working Distance	Auxiliary objective 2.0x, WD = 26mm.
	100mm. Can be adjusted to 26mm, 47mm or 177mm if auxiliary lens is used.
Focusing Holder	Coarse Ø76mm focus holder, 50mm focus range, fits Ø32mm pillar.
	Coarse and fine Ø76mm focus holder, 50mm focus range, fits Ø32mm pillar.
Stands	TS track stand with ergonomic base. Vertical travel of 110mm. Includes Ø76mm coarse focus holder.
	ILS2 reflected and transmitted LED light track stand with ergonomic base. Top LED light has 15 LEDs. Rheostat control for both lights. Includes Ø76mm coarse focus holder. 110~240V.
	LPS low profile base post stand.
	BMSQ boom stand on large square base with arbor.
	AASQ articulated arm stand on square base with arbor.
	AAC articulated arm clamping stand with arbor.
	BBSQ ball bearing boom stand on large square base with arbor.
Illuminators	BBC ball bearing clamping stand with arbor.
	LDG dual pipe LED light available as stand alone or clamping for track stand or post stand. Each self-supporting pipe is 24". 110~240V.
	LEDR/4 LED ring light with 4-quadrant control. 72 LEDs, variable intensity. 100~240V.
	MW151P 150w halogen light box with dual pipe lights. Each self-supporting light guide is 21". 110~240V.
Ring Light Adapter	MW151R 150w halogen light box with ring light. Flexible light guide is 40". 110~240V.
	RLA ring light adapter for connecting LED and halogen ring lights to FZ6 body.
Reflected Illumination	MW153R high intensity 35w LED light box with ring light. Flexible light guide is 40". 110~240V.